



# Tapes & Adhesives

## Spray Adhesives & Cleaners

### 3M™ hIPA Clean 300

An Isopropyl Alcohol (IPA) spray that cleans surfaces prior to the application of a 3M™ tape or adhesive, particularly 3M™ VHB™ Tape.

Size	Grade	Part Number	Ordering Code
300g	Isopropyl Alcohol Cleaner	300	AS010418940



### 3M™ Adhesive Cleaner and Solvent 700

Versatile general use solvent in aerosol form. Ideal for cleaning heavily contaminated surfaces prior to bonding, removal of adhesive residue or dismantling of previously bonded articles.

Size	Grade	Part Number	Ordering Code
350g	Adhesive Cleaner & Solvent	700	AS010426299



### 3M™ Foam Fast 74 Adhesive

Excellent for bonding foams & urethanes together and to many other materials like wood, metal and plastics. bonds immediately with long bonding range. Precise spray pattern. Colour - Pale orange

Size	Grade	Part Number	Ordering Code
489g	Foam Fast	74	62493549216



### 3M™ Super 77™ Multi-Purpose Adhesive

High tack, high coverage, fast-drying transparent adhesive for permanently attaching foils, carpeting, many lightweight foams, paper and fabrics to painted or unpainted metals, woods and other base materials. Multi-purpose product with high grab and sufficient open time to allow positioning of materials.

Size	Grade	Part Number	Ordering Code
467g	Multi Purpose	77	62443749213



Angle Grinders

Sanders

Hand Sanding

Belt Machines

Die Grinders

Fillet Weld Grinders

Bench Motors

3M Air Tools

3M Accessories

Tapes &amp; Adhesives

Paint Finishing

Safety

# Spray Adhesives & Cleaners

## 3M™ Rubber & Vinyl 80 Spray Adhesive

Exceptional resistance to plasticising oils, bonds rubber and supported vinyls better than many typical bulk neoprene contact adhesives. High heat resistance with a 30 minute open time. Precise spray pattern. Excellent plasticiser resistance. Colour - Yellow.

Size	Grade	Part Number	Ordering Code
539g	Rubber & Vinyl	80	62499649556



## 3M™ High Strength 90 Adhesive

A high strength fast contact-type adhesive. Excellent adhesive for decorative laminates, particleboard and many other materials including polyethylene, polypropylene and SBR rubber. 1-2 minutes drying time only. Colour - Translucent.

Size	Grade	Part Number	Ordering Code
500g	High Strength	90	62494249212



## Scotch-Weld™ Instant Adhesive

Bonds problem surfaces such as most EPDM rubbers, plastics, aluminiums and vinyls. Low viscosity. High strength. Very fast setting.

Size	Grade	Part Number	Ordering Code
28g	Instant Adhesive	CA-40	62380303305



# Industrial Tapes

## 3M™ Aluminium Foil Tape 425

3M™ Aluminium Foil Tape 425 has a dead-soft aluminium foil backing along with excellent heat and light reflection to protect against high temperatures and U.V. degradation. The foil also serves as an excellent barrier against moisture, dust, flame, and certain chemicals. Acrylic adhesive supplies superior temperature, U.V. and solvent resistance. It provides excellent age life and is ideal for harsh, long-term outdoor environments.



Size	Colour	Part Number	Ordering Code
12mm x 55m	Silver	425	70008500665
25mm x 55m	Silver	425	70008500640
38mm x 55m	Silver	425	70008500574
50mm x 55m	Silver	425	70008500582
75mm x 55m	Silver	425	70008500608
96mm x 55m	Silver	425	70008501234

## 3M™ High Performance Masking Tape 401+

3M™ High Performance Green Masking Tape 401+ was designed to deliver super-sharp paint lines where surface temperatures can reach up to 250 degrees F/ 121 degrees C. This green crepe paper tape is ideal for critical paint masking applications in automotive, specialty vehicle and industrial markets, where strong holding and high temp performance is required.



Size	Colour	Part Number	Ordering Code
12mm x 55m	Green	401+	70006745684
18mm x 55m	Green	401+	70006745692
24mm x 55m	Green	401+	70006745700
36mm x 55m	Green	401+	70006745718
48mm x 55m	Green	401+	70006745726

## 3M™ Temflex™ 1610 General Purpose Vinyl Electrical Tape

A general purpose vinyl insulating tape designed for use in phase identification, colour coding of motor leads and piping systems and for marking safety areas. It has very good resistance to abrasion, moisture, alkalis, acids and varying weather conditions. Operating temperature of up to 80°C. Thickness is 0.15 mm. Dielectric strength 39.4 kV/mm. Breaking strength is 2.8 kN/m.

Rainbow pack (3 x Black, 2 x White, 2 x Blue, 2 x Red, 1 x Green/Yellow).



Size	Colour	Part Number	Ordering Code
19mm x 20m	Orange	1610	AE019312329
19mm x 20m	Grey	1610	AE019312394
19mm x 20m	Blue	1610	AE010586749
19mm x 20m	Green/Yellow	1610	AE010586723
19mm x 20m	White	1610	AE010586756
19mm x 20m	Black	1610	AE010586764
19mm x 20m	Red	1610	AE010586731
19mm x 20m	Rainbow Pack	1610	AE010601407

- Angle Grinders
- Sanders
- Hand Sanding
- Belt Machines
- Die Grinders
- Fillet Weld Grinders
- Bench Motors
- 3M Air Tools
- 3M Accessories
- Tapes & Adhesives
- Paint Finishing
- Safety