


TORQUE WRENCH
STANLEY TORQUE WRENCH - HIGH ACCURACY 3%
STANLEY TORQUE WRENCH




- ISO 6789, ASME B107.14
- Accuracy: +/- 3%
- Visual and audible indication
- Dual way direction (C.W./C.C.W.) click type
- Quick release button
- Adjusting ring locking system
- Aluminium alloy handle with anodic treatment
- Si-Cr-Mo spring
- Cr-Mo pawl
- Cr-Mo square driver
- 48 Gear teeth



HSN CODE: 82041120
 MOQ:1

SKU #	DESCRIPTION	DRIVE SIZE	TORQUE RANGE	TORQUE RANGE	INCREMENT	B (mm)	L (mm)	WEIGHT (Kg)	MRP
STMT73587-1-8	1/4" TORQUE WRENCH 5-25 NM 3% AC	1/4"	5-25 N-m	48.7-225.7 in-lb	0.1 N-m	22.5	246	0.365	11,312
STMT73588-1-8	3/8" TORQUE WRENCH 10-50NM 3% AC	3/8"	10-50 N-m	9.2-38.7 Ft-lb	0.5 N-m	31	409	1.182	11,665

1/2" RATCHETING TYPE TORQUE WRENCH




- ISO 6789, ASME B107.14
- Accuracy: +/- 3%
- Visual and audible indication
- Dual way direction (C.W./C.C.W.) click type
- Dual scale (N-m & in-lb.)
- Quick release button
- Adjusting ring locking system
- Aluminium ring locking system
- Aluminium alloy handle with anodic treatment
- Si-Cr-Mo spring
- Cr-Mo pawl
- Cr-Mo square driver
- 48 Gear teeth



HSN CODE: 82041120
 MOQ:1

SKU #	DESCRIPTION	DRIVE SIZE	TORQUE RANGE	TORQUE RANGE	INCREMENT	B (mm)	L (mm)	WEIGHT (Kg)	MRP
STMT73589-1-8	1/2" TORQUE WRENCH 20-100NM 3% AC	1/2"	20-100 N-m	16.6-75.6 FT-lb	0.5 N-m	31	409	1.19	12,184
STMT73590-1-8	1/2" TORQUE WRENCH 40-200Nm 3% AC	1/2"	40-200 N-m	33.2-151.2 FT-lb	1 N-m	41	519	1.6	12,642
STMT73591-1-8	1/2" TORQUE WRENCH 60-340Nm 3% AC	1/2"	60-340 N-m	51.6-258.1 FT-lb	2 N-m	41	610	1.785	13,692

3/4" RATCHETING TYPE TORQUE WRENCH



- ISO 6789, ASME B107.14
- Accuracy: +/- 3%
- Visual and audible indication
- Dual way direction (C.W./C.C.W.) click type
- Quick release button
- Adjusting ring locking system
- Aluminium alloy handle with anodic treatment
- Si-Cr-Mo spring
- Cr-Mo pawl
- Cr-Mo square driver
- 48 Gear teeth




HSN CODE: 82041120
 MOQ:1

SKU #	DESCRIPTION	DRIVE SIZE	TORQUE RANGE	TORQUE RANGE	INCREMENT	B (mm)	L (mm)	WEIGHT (Kg)	MRP
STMT73592-1-8	3/4" TORQUE WRENCH 150-750Nm 3% AC	3/4"	150-750 N-m	110-550 Ft-lb	2.5 N-m	58	1112	5.87	43,613

STANLEY TORQUE WRENCH

1/4" & 3/8" RATCHETING TYPE TORQUE WRENCH




- ISO 6789, ASME B107.14
- Accuracy: +/- 4%
- Visual and audible indication
- Dual way direction (C.W./C.C.W.) click type
- Quick release button
- Adjusting ring locking system
- Aluminium alloy handle with anodic treatment
- Si-Cr-Mo spring
- Cr-Mo pawl
- Cr-Mo square driver
- 48 Gear teeth



HSN CODE: 82041120
MOQ:1

SKU #	DESCRIPTION	DRIVE SIZE	TORQUE RANGE	TORQUE RANGE	INCREMENT	B (mm)	L (mm)	WEIGHT (Kg)	MRP
STMT73587-8	1/4" TORQUE WRENCH 5-25 NM	1/4"	5-25 N-m	48.7-225.7 in-lb	0.1 N-m	22.5	246	0.365	9,865
STMT73588-8	3/8" TORQUE WRENCH 10-50NM	3/8"	10-50 N-m	9.2-38.7 Ft-lb	0.5 N-m	31	409	1.182	10,474

1/2" RATCHETING TYPE TORQUE WRENCH




- ISO 6789, ASME B107.14
- Accuracy: +/- 4%
- Visual and audible indication
- Dual way direction (C.W./C.C.W.) click type
- Dual scale (N-m & in-lb.)
- Quick release button
- Adjusting ring locking system
- Aluminium ring locking system
- Aluminium alloy handle with anodic treatment
- Si-Cr-Mo spring
- Cr-Mo pawl
- Cr-Mo square driver
- 48 Gear teeth



HSN CODE: 82041120
MOQ:1

SKU #	DESCRIPTION	DRIVE SIZE	TORQUE RANGE	TORQUE RANGE	INCREMENT	B (mm)	L (mm)	WEIGHT (Kg)	MRP
STMT73589-8	1/2" TORQUE WRENCH 20-100NM	1/2"	20-100 N-m	16.6-75.6 FT-lb	0.5 N-m	31	409	1.19	10,770
STMT73590-8	1/2" TORQUE WRENCH 40-200NM	1/2"	40-200 N-m	33.2-151.2 FT-lb	1 N-m	41	519	1.6	11,985
STMT73591-8	1/2" TORQUE WRENCH 60-340NM	1/2"	60-340 N-m	51.6-258.1 FT-lb	2 N-m	41	610	1.785	12,584

3/4" RATCHETING TYPE TORQUE WRENCH



- ISO 6789, ASME B107.14
- Accuracy: +/- 4%
- Visual and audible indication
- Dual way direction (C.W./C.C.W.) click type
- Quick release button
- Adjusting ring locking system
- Aluminium alloy handle with anodic treatment
- Si-Cr-Mo spring
- Cr-Mo pawl
- Cr-Mo square driver
- 48 Gear teeth



HSN CODE: 82041120
MOQ:1

SKU #	DESCRIPTION	DRIVE SIZE	TORQUE RANGE	TORQUE RANGE	INCREMENT	B (mm)	L (mm)	WEIGHT (Kg)	MRP
STMT73592-8	3/4" TORQUE WRENCH 150-750 NM	3/4"	150-750 N-m	110-550 Ft-lb	2.5 N-m	58	1112	5.87	41,406

BRITOOOL TORQUE WRENCH

3/8" CLASSIC TORQUE WRENCH



HSN CODE: 82041120

PART No.	DESCRIPTION	TORQUE RANGE	LENGTH	MOQ	MRP
AVT100A	3/8" SQ. DR. TORQUE WRENCH	(2.5-11Nm)	318MM	1	13,987
AVT300A	3/8" SQ. DR. TORQUE WRENCH	(5-33Nm)	422MM	1	14,208

1/2" CLASSIC TORQUE WRENCH



HSN CODE: 82041120

PART No.	DESCRIPTION	TORQUE RANGE	LENGTH	MOQ	MRP
EVT600A	1/2" SQ DR TORQUE WRENCH	12-68Nm	476MM	1	14,875
EVT1200A	1/2" SQ DR TORQUE WRENCH	25-135Nm	546MM	1	15,797
EVT2000A	1/2" SQ DR TORQUE WRENCH	50-225Nm	597MM	1	16,479
EVT3000A	1/2" SQ DR TORQUE WRENCH	70-330Nm	825MM	1	18,725

3/4" & 1" CLASSIC TORQUE WRENCH



HSN CODE: 82041120

PART No.	DESCRIPTION	TORQUE RANGE	LENGTH	MOQ	MRP
HVT5000	3/4" SQ DR TORQUE SPANNER	140-560Nm	1130MM	1	45,540
HVT7200	3/4" SQ DR TORQUE SPANNER	200-810Nm	1181MM	1	46,543
GVT8400	1" SQ DR TORQUE SPANNER	480-940Nm	1397MM	1	82,141

ACCESSIBILITY
Compact design ideal for restricted access

DURABILITY
Proven to be one of the most robust products in the market, the first choice for arduous conditions

ACCURACY
Exceeds requirements of ISO 6789

SCALE
Multiple scales – Nm, kg.m, lbf.in and lbf.ft are branded into steel tube, giving reliability for the life of the product

FLEXIBILITY
Push-through square drive for left- and right-hand operation

SETTING
Retractable adjuster knob cannot be altered by accident

SERVICE
Fully repairable with dedicated service kits